

ATTENZIONE - ATTENTION - ACHTUNG

- Per lo smontaggio degli utensili utilizzare sempre la chiave di contrasto come indicato nel manuale d'uso.
- For disassembly of the tools use always the contrast key as mentioned in the user instructions.
- Fuer das Abmontieren der Werkzeuge immer den Gegenschlüssel benutzen wie in der Bedienungsanleitung erwäehnt.

- Chiave inclusa
- Key included
- Schlüssel inbegriffen

Cod. MT	Mandrino Spindle Spindel	I	RPM	Coppia Max Max Torque Max Drehmoment	Reversibile lato mandrino/contromandrino Reversible sub/main spindle side Umkehrbare Spindel-seite/Gegenspindel-seite	Lubr.interna Coolant through Innenkuehlung	Lubr. esterna Ext. coolant Ausenkuehlung	A	A1	B	D	L	CHIAVI NON INCLUSE Keys not included Schluesel nicht einbegriffen	
NKM0061620	ER20	1:1	6000	50Nm	X		X	80.16	-	48	-	-	CHUB36	CHSTER20
NKM0061820	ER20	1:1	6000	50Nm	X	P=70bar	X	80.16	-	57.5	-	-	CHUB36	CHSTER20
NKM0061420	ER A 20	1:1	6000	50Nm	X		X	69.23	-	48	-	-	CHUB36	CHUB22
NKM0061425	ER25	1:1	6000	50Nm	X		X	80.16	-	48	-	-	CHUB36	CHSTER25
NKM0061625	ER25	1:1	6000	50Nm	X	P=70bar	X	80.16	-	59	-	-	CHUB36	CHSTER25
NKM0062432	ER32	1:1	6000	50Nm	X		X	92.16	-	48	-	-	CHUB36	CHSTER32
NKM0062532	ER32	1:1	6000	50Nm	X	P=70bar	X	92.16	-	57.5	-	-	CHUB36	CHSTER32
NKM0061617	Ø16x17	1:1	6000	50Nm	X		X	-	63	48	16	17	CHUB36	CH_VTCROCE_M08 ▪
NKM0062219	Ø22x19	1:1	6000	50Nm	X		X	-	63	48	22	19	CHUB36	CH_VTCROCE_M10 ▪
NKM0062721	Ø27x21	1:1	6000	50Nm	X		X	-	65.5	48	27	21	CHUB36	CH_VTCROCE_M12 ▪

NAKAMURA - TOME


WT250 - WT15011/25011 - WTW150 - WTS150 - SC150/200/250 - SUPER NTJX - NTY3 150/250 - AS200 15 ST.

MODULO MOTORIZZATO ASSIALE H=75mm

Axial driven tool H=75mm

Axial angetriebenes Werkzeug H=75mm

Subject to change without notice.



M.T. srl

Via Casino Albini 480
Tel. 0541/956034-957884
Fax 0541/956341
47842 S. GIOVANNI IN M. (RN)
e-mail: mtma@mtmarchetti.com
http://www.mtmarchetti.com

PRODUZIONE MODULI ROTANTI



PAGINA NKM150-2-20